LT-CBL-GRND-1/2L-KIT

SPRING TYPE OUTDOOR GROUNDING KIT FOR 1/2" FLEXIBLE RF CABLE

The LT-CBL-GRND-1/2L-KIT is a grounding kit designed for 1/2" RF coaxial cables, providing effective lightning protection and electrical grounding. This long-type kit ensures secure attachment and reliable grounding to protect communication equipment from surges and electrical faults.

Key Features

- Designed for 1/2" RF coaxial cables
- Provides effective grounding and lightning protection
- Long-type strap ensures secure and stable contact
- Corrosion-resistant materials for long-term reliability
- · Easy to install with included components
- · Enhances overall system safety and performance

Key Highlights

- Suitable for indoor and outdoor RF installations
- Maintains low contact resistance over time
- Compatible with standard grounding bars and kits
- Flexible design allows quick installation in tight spaces
- Supports industry-standard grounding practices

Applications

- Telecom towers and base stations
- RF feeder cable routing in outdoor enclosures
- · Broadcast and antenna systems
- DAS (Distributed Antenna Systems) installations
- Rooftop and pole-mounted equipment setups
- · Indoor cable tray and rack management
- Wireless communication infrastructure





Specifications

| Item | GKS Type | |
|-----------------------------------|------------------------------------|-------------------|
| Grounding Wire Length | 0.6M | |
| Cable Section Acreage | 16mm ² | |
| Stretching Resistance | >500N | |
| Contact Material | Copper + 304(ASTM) Stainless steel | |
| Resistance | ≤3mΩ | |
| Voltage Resistance | 80kA | |
| Power Frequency WithStand Voltage | 35k | V |
| Insulation Resistance | 10GΩ | |
| Earth Resistance | 2mΩ | |
| Operating Temperature | -40~+70 | |
| Suitable Cable | 1/2" flexible RF cable | |
| Description | Rubber Mastic Tape | Electrical Tape |
| Size | 60mm*2.50mm*600mm | 19mm*0.18mm*20m |
| Color | Black | Black |
| Tensile Strength | 1.03~1.65 N/mm ² | >40 N/mm2 |
| Breakdown Elongation | ≥750 % | >200 % |
| Stickiness | 17~ 22 N/10mm | 4~8 N/10mm |
| Heat Resistance | 70 /168 h | 70 /168 h |
| RoHS | Yes | Yes |
| Temperature Range | -40 ∼ +70 | -10 ~ +105 |

