

LT-ANT118-132-5

Fiberglass Omni Base Antenna | 118-132 MHz | 5 dBi

Features

- Superior Performance
- Sealed with Fiberglass
- All Weather Operation
- N Female Connector
- Tube Packing
- Compatible Clamp: LT-C/ANT-BU (sold separately)

Applications

- 118-132 MHz VHF System
- Electronics Navigation Systems
- Remote Sensing & Telemetry

Specifications

| LT-ANT118-132-5 | |
|--------------------|-----------------|
| Frequency Range | 118-132 MHz |
| Antenna Gain | 5 ± 1 dBi |
| Power Rating | 500 W |
| Impedance | 50 Ω |
| VSWR | ≤ 1.6 |
| Pattern | Omnidirectional |
| Vertical Beamwidth | 35° |

| LT-ANT118-132-5 | |
|--------------------------|-------------------|
| Termination | N Female |
| Dimensions (mm) | Φ 70* (4000 ± 20) |
| Packing Dimensions (mm) | Φ 94* (4450 ± 20) |
| Weight with Bracket (Kg) | 5.78 ± 0.2 |
| Fiberglass Color | Blue |
| Wind Rating (0.5" ice) | 37.45KgF |
| Maximum Exposed Area | 3.01 ft² |
| Wind Velocity | 60m/s |

