# LT-OTR-4G2S

### **OUTDOOR 4G ROUTER DUAL-SIM**

Integrated mobile modem, the LT-OTR-4G2S outdoor 4G router connect your phone, tablet, computer, camera, etc. to the internet via WiFi or LAN Ethernet. Comes with MIMO antennas, the router receive signals at a high sensitivity. Complying with the IEEE 802.11b/g/n standard, the outdoor router output Wi-Fi signals at max 27dBm power with transmission speeds of up to 300Mbps. You can control the Wi-Fi and LAN networks with firmware, such as SSID, DNS, encryption, firewall, port forwarding, Wi-Fi relay, and so on. IP67 hardened industrial-grade aluminum alloy case enclosure the router to withstand extreme weather conditions and rugged deployments.





DUAL-SIM CARD HOLDER



### Features:

#### MIMO 3G/4G Mobile Modem



- ▲ MIMO 4G High sensitivity
- ▲ Replaceable mini PCIe modem
- ▲ Multiple standard modems available



#### MIMO 3G/4G Mobile Modem

- ▲ PoE support IEEE 802.3af/at
- ▲ PoE injector included
- ▲ Support 50-100 meters LAN cable

#### MIMO Wi-Fi with Booster



- ▲ 2.4GHz IEEE 802.11b/g/n & 802.3u
- ▲ Wi-Fi transmission rate up to 300Mbps
- ▲ Support up to 57 concurrent users



#### **Industrial-grade Rugged Design**

- Designed for rugged deployments
- ▲ IP67 hardened aluminium alloy case
- ▲ Surge protection



# LT-OTR-4G2S

## **OUTDOOR 4G ROUTER DUAL-SIM**

# **Specifications:**

Hardwares					
CPU	Qualcomm Atheros QCA9531				
Frequency	650 MHz				
Memory	128 MB				
Flash	16 MB				
	Frequecy: 698~960 / 1710~2700MHz				
4G Omni Antenna	Gain: 3/4/3.5 dBi				
	V.S.W.R.: ≤ 2.0				
	Frequency: 2400~2500MHz				
2.4G Wi-Fi Antenna	Gain: 5 dBi				
	V.S.W.R.: ≤ 2.0				
2 x SIM card slot	Nano SIM card (12.3x8.8mm)				
RJ45 port	1 x 10/100Mbps				
Indicator	System / WiFi / SIM1 / SIM2				
Temperature	Working: -40 to 80°C				
	Storage: -50 to 90°C				
Working humidity	10%-90% RH				
Installation	Pole mounted				
Firmwares					
Concurrent users	57 users				
Bootloader	LTBoot				
Firmware	OpenELT				
Computer support	Windows / Mac / Linux				

Wi-Fi Router					
Standards	IEEE 802.11 b/n/g & 802.3u				
Transmission rate	e 300Mbps by 2T2R MIMO				
Frequency	2412~2484 MHz				
Channel	1~13				
Bandwidth	20/40MHz or Auto				
Output power	802.11n: 23±2dBm for OFDM mode				
	802.11g: 25±2dBm for OFDM mode				
	802.11b: 27±2dBm for CCK mode				
Wi-Fi modes	11b / 11g / 11n only				
	11 b/g mixed				
	11 b/g/n mixed				
PoE (power over	r Ethernet)				
PoE power	48Volt				
PoE standard	802.3af/at				
Cable length	50~100 meters				
Wiring	Ethernet 1,2,3,6 / DC+ 4,5 / DC- 7,8				

### 3G/4G MODEMS:

4GLTE	
Download	150Mbps
Upload	50Mbps
3GHSPA+	
Download	21Mbps
Upload	5.76Mbps
3GTD-SCDMA	
Download	2.8Mbps
Upload	2.2Mbps
CAT.6 -Transn	nission Rate
4GLTE	
Download	300Mbps
Upload	50Mbps

### **CAT. 4 - Transmission Rate**

-EU-x	-AOS-x	-NA-x
EU/UK - Standard	Oceanian Standard	American Standards

Supported Mobile Frequency		Supported Mobile Frequency		Supported Mobile Frequency		
4G FDD LTE	B1/B3/B5/B7/B8/B20	4G FDD LTE	B1/B2/B3/B4	4GFDD LTE	B2/B4/B5/B12	
4G TDD LTE	B38/B40/B41		B5/B7/B8/B28		B13/B14/B66/B71	
3G WCDMA	B1/B5/B8	4G TDD LTE	B40	3G WCDMA	B2/B4/B5	
2G GSM	B3/B8	3G WCDMA	B1/B2/B5/B8			
		2G GSM	B2/B3/B5/B8			
Country	Country					
Europe		Australia, New Zealand		North America		
Africa	Philippines, Brazil, Argentina		rgentina	(Canada, United States)		
Most countries in Asia Colom		Colombia etc.	Colombia etc.		Some countries in America	
Certificate		Certificate		Certificate		
RCM/CE/ICASA/FAC/GCE		RCM/FCC/Anatel		GCF/FCC/IC/PTCRB		

