

LT-PS-330/2700-3W

3-Way Power Splitter | 330-2700 MHz | 4.8 dBi

The Lamatel LT-PS-330/2700-3W 3-Way Power Splitter is designed to evenly distribute RF signals across three output ports within the 330–2700 MHz frequency range. With a gain of 4.8 dBi, this splitter ensures minimal signal loss and balanced power division, making it ideal for use in distributed antenna systems (DAS), indoor and outdoor wireless networks, and communication infrastructure setups. Its compact and robust design allows reliable performance in various RF applications requiring consistent signal distribution.

Key Features

- Wide Frequency Range: 330–2700 MHz
- Coupling Value: 4.8 dB for accurate signal sampling
- Low Insertion Loss ensures minimal signal degradation
- High Isolation between input and output ports
- Durable Construction for reliable indoor and outdoor use
- Suitable for Distributed Antenna Systems (DAS), power monitoring, and signal testing applications

Key Highlights

- Excellent VSWR Performance for maximum system efficiency
- Bi-directional Design allows flexible installation options
- High Power Handling Capability for demanding RF environments
- Stable Performance Across Wide Temperature Ranges
- Corrosion-Resistant Finish ensures long-term reliability
- Easy Integration into existing RF communication and test setups

Applications

- Distributed Antenna Systems (DAS) for buildings, tunnels, and stadiums
- Signal Monitoring and Testing in RF communication systems
- Power Measurement in transmission lines



Specifications

Electrical Specifications	
Frequency	330-2700 MHz
Configuration	1:2
Split Loss	3.0 dB
Insertion Loss	0.30 dB
VSWR	≤1.25 @ 380-2700 MHz
	≤1.35 @ 330-380 MHz
Power Capacity	Avg. 300 W, Peak 3.0 kW
Impedance	50 Ω
Intermodulation	≤ -161 dBc @ 2 x 43 dBm
Environmental Specifications	
Environment	ETS 300 019
Operating Temperature	-25 °C to +85 °C
Relative Humidity	0 ~ 95%
Application	IP65
Mechanical Specifications	
Dimensions (mm)	143 x 25 x 25
Weight (Kg, N)	0.360
Weight (Kg, 4.3-10)	0.390
RF Connector	4.3-10 or N Female

