

LT-RF3G200WANMF50

200W RF Attenuator with Wide Frequency Range and Low VSWR

The LT-RF3G200WANMF50 is a high-power RF attenuator capable of handling up to 200 watts of power. Operating across a frequency range from DC to 3 GHz, it provides 50 dB attenuation with high accuracy and low VSWR, making it an excellent choice for in-building solutions and testing environments. This attenuator is equipped with N-Male to N-Female connectors and is designed to operate under extreme temperature conditions.



Key Features

- Wide Frequency Range: Operates from DC to 3 GHz, covering multiple communication bands.
- High Power Handling: Supports up to 200 watts of average power.
- Low VSWR: ≤ 1.35 for efficient signal performance and minimal reflection.
- Attenuation Level: Provides 50 dB of attenuation with a precision of ± 1.5 dB.
- Durable Connectors: N-Male to N-Female configuration for easy integration.
- Wide Temperature Range: Operates reliably from -55°C to $+125^{\circ}\text{C}$.


Key Highlights

- Compact and rugged design
- Excellent thermal management
- Stable performance across full range
- Ideal for lab, test, and telecom use
- Easy plug-and-play installation
- No maintenance required

Applications

- Wireless Communication Systems
- In-building Communication Solutions
- Laboratory Testing and Measurement
- Network Deployment and Maintenance

Mechanical Drawing



Specifications

Parameter	Value
Model Number	LT-RF3G200WANMF50
Frequency Range	DC - 3 GHz
Power Handling	200W
Attenuation	50 dB
Attenuation Accuracy	± 1.5 dB
VSWR	≤ 1.35
Impedance	50 Ohms
Connector Type	N-Male to N-Female
Color	Black
Operating Temperature	-55°C to $+125^{\circ}\text{C}$
Applications	In-building Solutions, Testing Environments, Wireless Communication Systems

